FOR SALE - Listing #OT423X

OTSUKA IRON WORKS 42" x 30"

SINGLE TOGGLE JAW CRUSHER

- OTSUKA IRON WORKS (now Furukawa) 42" x 30" Single Toggle Jaw
- Upto 300 tonnes per hour capacity.
- Dry toggle configuration with full adjustment.
- Jaws Plates and Wear Plates, Bearings, Eccentric shaft, swing jaw, toggles, pitman and main frame in good condition. Workshop checked and ready for work.



PRICE POA

Delivered Major Asian PortAQIS Cleaning, Loading and Shipping available at Cost.

PHONE: 0466 051 790 / 07 40549348

Price subject to change, unit is subject to availability and prior sale. All omissions and errors are excepted. Unit photographed is unit for sale.

Unit will be transported to major sea port for shipping. Cleaning and Loading maybe required and can be arranged at shippers cost.

FOR SALE – Listing #OT423X

OTSUKA – 42" x 30" SINGLE TOGGLE JAW CRUSHER



PHONE: 0466 051 790 / 07 40549348

Price subject to change, unit is subject to availability and prior sale. All omissions and errors are excepted. Unit photographed is unit for sale.

Unit will be transported to major sea port for shipping. Cleaning and Loading maybe required and can be arranged at shippers cost.

FOR SALE – Listing #OT423X

OTSUKA – 42" x 30" SINGLE TOGGLE JAW CRUSHER



PHONE: 0466 051 790 / 07 40549348

Price subject to change, unit is subject to availability and prior sale. All omissions and errors are excepted. Unit photographed is unit for sale.

Unit will be transported to major sea port for shipping. Cleaning and Loading maybe required and can be arranged at shippers cost.

FOR SALE - Listing #OT423X

2 CRUSHING

Type FS Single Toggle Crusher



Type FS Single Toggle Crusher employs a single reciprocating toggle for compressing the feed. Since this single toggle crusher is capable of crushing lumps as large as several hundred millimeters in diameter, it is used for primary and secondary crushing. Being simple in construction, the single toggle crusher requires a comparatively small installation space and is easy of maintenance and inspection.

The single toggle crushers of have a large crushing ratio and a rugged construction to assure stable crushing operation.



Hydraulic setting mechanism (option)

Model	Feed opening mm	Crushing capacity t/h Discharge clearance (open setting) mm											Motor
		FS-3020	750×500	48	53	72	98	117	138				
FS-3524	900×600	_ \		108	132	164	186						55~75
FS-4230	1050 × 750		-	177	186	217	245	284	304				75~110
FS-4340	1200 × 1000		W			275	312	348	382	416			110~130
FS-5142	1370×1050		ч	1		330	370	410	460	500	530		130~150
FS-6048	1500×1200						425	468	510	550	590	540	150~190
FS-7254	1800×1370						575	830	880	725	770	845	200~250
FS-8460	2100×1500							850	910	955	1000	1110	260~300

Type FSR Single Toggle Crusher

Type FSR Single Toggle Crusher can effectively be applied to a wide variety of materials, although it is most suitable to crush reinforced concrete. It is equipped with a device which automatically detects an unusual load caused by entry of foreign matter and prevents the crusher from jamming. The crusher can be operated and adjusted easily by pushbuttons. The lead time for delivery of standard consumable parts of the crusher is short.

Type F Single Toggle Crusher

Like Type FS, Type F Single Toggle Crusher employs a single reciprocating toggle for compressing the feed. Thanks to a small angle of inclination of the crushing chamber, the crusher is free from choking and capable of efficiently producing fine grains of uniform size.





Model	Feed opening mm	Crushing capacity t/h										
		Discharge clearance (closed setting) mm										
		10	15	50	25	30	40.	50	65	80	kW	
F-108	250×150	1,7	3.3	5.0	6.3						5.5	
F-158	380×200	3.1	6.2	9.0	115	14					-11	
F-209	510×230		8,5	12.5	16	19.2	25	-			15~19	
F-2410	610×250			16.5	22	27	34	41			19~22	
F-3012	760×300				30	35	46	55	68		30~-37	
F-3618	900×460					- 51	65	77	96	112	45~-55	
F-3624	900×800						78	93	113	130	55~75	

ROCK INDUSTRY PTY LTD



PHONE: 0466 051 790 / 07 40549348